

# Angekis®

---

## THE CURTANA

HD USB Conferencing camera  
Wide angle, USB 2.0

---

**£253 RRP\***



---

Distributed by TUKANS Ltd – [www.tukans.com](http://www.tukans.com) – 01904 720617

\*RRP excludes VAT. Pricing & information given in this specification sheet is correct at time of print and may change at any time.

# Features

---

## See

- 105° wide field of view
- 350° pan, -35° to +130° tilt
- Fixed lens
- Low noise CMOS sensor
- Low lighting ability

## Control

- RS-232 local VISCA support
- IR remote
- Far end camera control
- Presets via remote or RS-232

## Mount

- Mount using standard ¼" tripod screw
- Reverse/flip mountable
- G-Sensor automatically detects the camera rotation

## Connect

- Plug & Play USB 2.0
- Use instantly with soft codecs
- No extra hardware needed



# Specifications

Part number		U2-FFHD3
Application type		USB Video conferencing
Image Sensor	Type	OmniVision (OV) CMOS
	Size	1/2.7"
Megapixel count	Total / Effective	2.4 megapixels, 2.07 megapixels
Supported resolutions	USB output	1080p/30, 720p/30
Zoom		0x, fixed lens camera
Focus	Modes	Fixed Lens
	Focal Length	F=3.5mm
	Iris	F1.6
	Distance	100mm (wide
Shutter speed (sec)		1/10
Max pan rotation		±350°
Max pan control speed		0~128°/sec
Max tilt rotation		(-35°~ +130°)
Max tilt control speed		85°/sec
Field of view	Wide	105°
	Tele	-
Preset storage	IR remote	7 presets
	VISCA, RS232	256 presets
S/N ratio (dB)		>40dB
Image gain	Auto, Manual	Auto
White balance	Auto, Manual	Auto
Image flip		Yes, G-sensor for automated sensing
Illumination		Minimum: 0.8 Lux
Exposure control		Auto, Manual
Wide Dynamic Range		No
3D Noise Reduction		No
Video output interface		USB 2.0
PTZ control	Interface	RS-232C, RS-422
	Protocols	UVC, VISCA, PELCO P, PELCO D
Power supply		12 vDC
Power consumption		12 Watts
Storage temperature		-10°C ~ +45°C
Weight		1.1 KG
Dimensions	W x D x H	170 x 160 x 150mm
Warranty		

If you have any questions, contact us at [sales@tukans.com](mailto:sales@tukans.com) or on 01904 720617